



Fast hardening adhesive-sealant Torggler Sitol

Marine black 80ml



| | |
|--------------|---------------------------------------|
| Manufacturer | |
| Weight | 0.20 kg |
| Product Code | 501969 |
| SKU | 004224 |
| Advice IBB | |
| Application | Perfect for general immersion bonding |
| IBB ID | 14120 |

Product specification

| | | | |
|--------------|----------|------|-----|
| Manufacturer | Torggler | Unit | pcs |
|--------------|----------|------|-----|

Fast hardening adhesive-sealant based on hybrid polymers with high initial adhesion.

- UV, weather, chemical and saltwater resistant
- Adheres to wet and immersed substrates
- Free of solvents and isocyanates. It does not require training according to Annex XVII of Regulation (EC) 1907/2006
- Compatible with marine industry materials on deck/main deck and below deck

Sitol® Marine is a high-quality, professional adhesive-sealant based on hybrid polymers, certified by IMO MED. It hardens by reaction with moisture to form a permanently elastic mass. It has rapid hardening and high initial adhesion, permanent elasticity from -40 to +100 °C.

Absorbs vibrations and acoustically insulates bonded elements. It is resistant to UV radiation, ageing in general, chemicals and salt water. It does not shrink, it does not crumble. Solvent and isocyanate free. It adheres without primer to typical materials of the marine industry, natural and synthetic, smooth and porous, even wet, provided they are clean, degreased and compact. It adheres to wet or immersed substrates.

Sitol® Marine complies with the MED Directive and is certified by IMO Resolution MSC.307 (88) – Fire Testing Procedures Code (FTP Code 2010) – An. 1, part 5.

It also meets the European requirements for CE marking of sealants for applications on exterior and interior envelopes, pedestrian walkways and in environments constantly exposed to water.

EN 15651-1 F INT-EXT CC 20 HM

EN 15651-3 XS3 /

EN 15651-4 PW EXT-INT 20 HM