



# Metal frame fixing LO-10072 10x72mm 100pcs



Manufacturer	
Dimension	10x72mm
Weight	0.60 kg
Product Code	LO-10072
EAN	5907704410010
SKU	2515
Advice IBB	
Application	for fixing door and window frames
IBB ID	2515

## Product specification

Manufacturer	WKREŹ-MET	Unit	pack
EAN	5907704410010	Dimension	10x72mm
Coating	galvanized	Diameter [mm]	10
Drive type	pz-2		

The connector for LO door/window frames is made of carbon steel covered with a protective layer of zinc. The connector consists of an M6 threaded pin with a countersunk head and a PZ recess, an expansion cone screwed onto a threaded pin and an expansion sleeve. The connector is designed for the installation of door frames, steel anchors fixing the woodwork - to be used with a plastic plug in various colors. Types of substrates to which the LO door/window frame connector can be installed: • plain concrete • full ceramic brick • ceramic brick • silicate block Assembly method: 1. Before installation, it is necessary to identify the substrate in which the fastener will be installed and compare the loads that the fastener will carry with the load capacities contained in the Characteristics Data Sheet or in the National Technical Assessment 2. The appropriate length of the fastener should be selected so that the expansion zone is in the structural material of the wall (the thickness of the fastened element corresponds to the maximum usable length of the fastener - tfix) 3. The correct method of drilling should be used depending on the type of substrate (holes in the masonry substrate made of perforated elements should be drilled with a drill without impact) 4. The diameter of the drilled holes should be in accordance with the diameter of the hole recommended by the manufacturer 5. Holes in substrates made of solid materials should be deeper by min. 10 mm from the anchorage depth 6. Holes in solid materials should be cleaned of cuttings with a reciprocating movement with a drill at reduced speed 7. It is fixed by screwing in the screw, which expands the sleeve and permanently fixes it in the ground